

FLAGPOLE – MA-21-5 / MA-25-5

WINDSOCK 13"D-18"D-24"D

SHAFT

- 6061-T6 aluminium tube;
- MA-21-5 = 20'L x 3"D x 0.120"E;
- MA-25-5 = 23'L x 3"D x 0.120"E;
- Internal Nylon halyard 1/4";
- PVC lock, rope cleat, key;
- 8"L x 8"L x 3/4"E base 6061-T6 aluminium;
- Aluminium base cover, 2 pcs;
- Satin sand finish #100.

ROTATING HEAD

- 5"D swivel– UHMW;
- 6.5"D x 8"H decorative ball;
- 3/4" counterweight rod 6061-T6 aluminium;
- UHMW retaining ring.

WINDSOCK BRACKET

- 1/4" swelded stainless steel;
- 13"D or 18"D or 24"D maximum, 3/4" stainless steel, swivel;
- 1.75" x 3.5" UHMW sleeve;
- 2" x 1/4" UHMW washer.

WINDSOCK

- Nylon 200D DuPont SolarMax™ ;
- 13"D x 5'L or 18"D x 5'L or 24"D x 6'L maximum;
- Orange/White ou Orange.

OTHER OPTIONS

- Precast concrete base with anchors;
- Screw piles with anchors;
- Painted powder coated pole.

